

UHE0J153MHD

UHE0J153MHD Information

www.heispcer.com	Part Number Manufacturer Category Description Package	UHE0J153MHD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 15000UF 20% 6.3V RADIAL Radial, Can	
	Package	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHE0J153MHD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency3.376A @ 120HzImpedance14 mOhmsLied Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)3.398° (35.50mm)Surface Mount Land Size-Package / CaseKaial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLied Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UHE0J153MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolariGeneral PurposeRiple Current - Low Frequency3.376A @ 120HzRiple Current - High Frequency4.22A @ 100kHzImpedance0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUHECapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzInpedance1.4mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.295° (7.50mm)Height - Seated (Max)3.98° (35.50mm)Surface Mount Land Size-Mounting TypeFnought HolePackage / CaseKaila Can		Aluminum Electrolytic Capacitors
Capacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Series	UHE
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension1.398" (35.50mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	15000µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzBipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	8000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	3.376A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	4.22A @ 100kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	14 mOhms
Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.398" (35.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHE0J153MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE0J153MHD Payment Methods



UHE0J153MHD Shipping Methods



If you have any question about UHE0J153MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com