



UHE0J272MHT Information



For Reference Only

Part Number UHE0J272MHT

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2700UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHE0J272MHT Specifications

Manufacturer Part Number Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UHE Capacitance 2700µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications Ripple Current - High Frequency Light of the series and th		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance2700μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.552A @ 120Hz	Manufacturer Part Number	UHE0J272MHT
PackageRadial, CanSeriesUHECapacitance2700μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.552A @ 120Hz	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance2700μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105 °COperating Temperature-40 °C ~ 105 °CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.552A @ 120Hz	Category	Capacitors
SeriesUHECapacitance $2700\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $6.3V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $8000 \text{ Hrs @ } 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1.552A @ 120\text{Hz}$		Aluminum Electrolytic Capacitors
Capacitance $2700\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $6.3V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1.552A @ 120\text{Hz}$	Package	Radial, Can
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.552A @ 120Hz	Series	UHE
Voltage - Rated6.3 VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.552A @ 120Hz	Capacitance	2700μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.552A @ 120Hz	Tolerance	±20%
Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.552A @ 120Hz	Voltage - Rated	6.3V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.552A @ 120Hz	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.552A @ 120Hz	Lifetime @ Temp.	8000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.552A @ 120Hz	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency 1.552A @ 120Hz	Polarization	Polar
	Applications	General Purpose
Ripple Current - High Frequency 1 94A @ 100kHz	Ripple Current - Low Frequency	1.552A @ 120Hz
rappie current Tright requency 1.74A @ 100kHz	Ripple Current - High Frequency	1.94A @ 100kHz
Impedance 42 mOhms	Impedance	42 mOhms
Lead Spacing 0.295" (7.50mm)	Lead Spacing	0.295" (7.50mm)
Size / Dimension 0.630" Dia (16.00mm)	Size / Dimension	0.630" Dia (16.00mm)
Height - Seated (Max) 0.591" (15.00mm)	Height - Seated (Max)	0.591" (15.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UHE0J272MHT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE0J272MHT Payment Methods



















UHE0J272MHT Shipping Methods













If you have any question about UHE0J272MHT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com