

# UHE0J682MHD

Request a Quote

## **UHE0J682MHD** Information

	Part Number	UHE0J682MHD	
	Manufacturer	Nichicon	
w beisener.com	Category	Capacitors Aluminum Electrolytic Capacitors	
-//	Description	CAP ALUM 6800UF 20% 6.3V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UHE0J682MHD Specifications**

Manufacturer Part NumberUHE01682MHDManufacturer ANichiconCategoryCapacitorsAtminum Electrolytic CapacitorsPackageRdial, CanStriesUHECapacitance6800µFOlarace6200µCVoltage - Rated6.3V AESR (Equivalent Series Resistance)-Lifetime Ø Temp,8000 Hrs @ 105°COperating Temperature900 Hrs @ 105°CPolarization901 ArrApplicationsGeneral PurposeRipple Current - High Frequency3.35 A @ 100 HrzIppedance107°C (500mn)Size J Dimension902°D in (1.50mn)Size J Dimension9.492°D in (1.50mn)Surface Mount Land Size-Mounting TypeHroug HolePackage Case-Rounting TypeArouge HolePackage Case-Mounting TypeHroug HolePackage Case-Package Case-Pa	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature90arOperating Temperature90arApplicationsGeneral PurposeRippe Current - High Frequency3.55A @ 100kHzImpedance1.7mOhmsLiad Spacing0.197" (5.00mm)Size / Dimension1.575" (40.00mm)Height - Seated (Max).575" (40.00mm)Surface Mount Land Size-Nounting TypeFrough HolePackage / CaseKadia, Can	Manufacturer Part Number	UHE0J682MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications2.68A @ 120HzRipple Current - Low Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension1.575" (40.00mm)Surface Mount Land Size-Mounting TypeRadial, CanPackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance6800µFTolerance-20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplications2.68A @ 120HzRipple Current - Low Frequency3.35A @ 100kHzImpedance0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Siz / Dimension5.75" (40.00mm)Sirafee Mount Land Size-Mounting TypeFinough HolePackage / CaseKadial, Can	Category	Capacitors
SeriesUHECapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzImpedance17 mOhmsLiad Spacing0.197° (5.00mm)Size / Dinension0.492° Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePotarge CraseMounting TheorementSurface Mount Land Size-Mounting TypeRatial, Can		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRippe Current - Hugh Frequency3.35A @ 100kHzImpedance17 mOhmsLad Spacing0.197°(5.00mm)Size / Dimension1.575°(4.00mm)Surface Mount Land Size-Mounting TypeThrough HolePolarized Maximum Capacitation1.575°(4.00mm)Surface Mount Land SizeForugh HolePolarized Maximum Capacitation1.575°(4.00mm)Surface Mount Land SizeForugh HolePolarized Maximum Capacitation1.575°(4.00mm)Surface Mount Land SizeSatal All All All All All All All All All A	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzImpedance17 mOhnsLead Spacing0.197" (5.00mm)Size / Dimension1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UHE
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzRipple Current - High Frequency3.35A @ 100kHzLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	6800µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzRipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.8000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzRipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzBipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzRipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	8000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.68A @ 120HzRipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency2.68A @ 120HzRipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency3.35A @ 100kHzImpedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance17 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.68A @ 120Hz
I card Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.35A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	17 mOhms
Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.575" (40.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UHE0J682MHD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UHE0J682MHD Payment Methods**



# **UHE0J682MHD Shipping Methods**



If you have any question about UHE0J682MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com