

# UHE1C222MHD

## **UHE1C222MHD Information**

w deisener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 2200UF 20% 16V RADIAL Radial, Can	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **UHE1C222MHD Specifications**

Manufacturer Nichicon   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can   Series UHE   Capacitance 2200µF   Tolerance ±20%   Voltage - Rated 16V   ESR (Equivalent Series Resistance) -   Lifetime @ Temp. 10000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization General Purpose   Riple Current - Low Frequency 2.304A @ 120Hz   Ripple Current - High Frequency 2.304A @ 120Hz   Impedance 27 mOhms   Lead Spacing 0.197" (5.00mm)   Size / Dimension 0.492" Dia (12.50mm)   Height - Seated (Max) 0.984" (25.00mm)   Surface Mount Land Size -   Mounting Type Through Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUHECapacitance200µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.304A @ 100kHzImpedance0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UHE1C222MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance2200µFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.33A @ 100kHzImpedance0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Size / Dimension-Mounting TypeThrough HolePackage / CaseRatial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance2200μFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.304A @ 100kHzSize / Dimension0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Surface Mount Land Size-Mounting TypeAradia, CanPackage / CaseRadia, Can	Category	Capacitors
SeriesUHECapacitance2200µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.984" (25.00mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzImpedance27 mOhmsLied Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.304A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UHE
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	2200µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	16V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max).9844" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency2.304A @ 120HzRipple Current - High Frequency2.23A @ 100kHzImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
In restriction27 mOhmsImpedance27 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.304A @ 120Hz
I can be can b	Ripple Current - High Frequency	2.23A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	27 mOhms
Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.984" (25.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### **UHE1C222MHD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UHE1C222MHD Payment Methods**



## **UHE1C222MHD Shipping Methods**



If you have any question about UHE1C222MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com