



UHE1E331MPD Information



For Reference Only

Part Number UHE1E331MPD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHE1E331MPD Specifications

Manufacturer Part NumberUHE1E331MPDManufacturerNichiconCategoryCapacitorsPackageRadial, CanSeriesUHECapacitance330µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency588mA @ 120HzRipple Current - High Frequency840mA @ 100kHzImpedance87 mOhms
CategoryCapacitorsPackageRadial, CanSeriesUHECapacitance330μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency588mA @ 120HzRipple Current - High Frequency840mA @ 100kHz
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance330μFTolerance±20%Voltage - Rated25 VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105 °COperating Temperature-40 °C ~ 105 °CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency588mA @ 120HzRipple Current - High Frequency840mA @ 100kHz
PackageRadial, CanSeriesUHECapacitance330μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency588mA @ 120HzRipple Current - High Frequency840mA @ 100kHz
SeriesUHECapacitance $330μF$ Tolerance $±20%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $7000 Hrs @ 105°C$ Operating Temperature $-40°C \sim 105°C$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $588mA @ 120Hz$ Ripple Current - High Frequency $840mA @ 100kHz$
Capacitance $330μF$ Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $7000 \text{ Hrs @ }105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $588mA @ 120Hz$ Ripple Current - High Frequency $840mA @ 100kHz$
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 588mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency S88mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
ESR (Equivalent Series Resistance) Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 588mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 588mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S88mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 588mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Applications General Purpose Ripple Current - Low Frequency 588mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Ripple Current - Low Frequency 588mA @ 120Hz Ripple Current - High Frequency 840mA @ 100kHz
Ripple Current - High Frequency 840mA @ 100kHz
Impedance 97 mOhms
Impedance 87 mOhms
Lead Spacing 0.138" (3.50mm)
Size / Dimension 0.315" Dia (8.00mm)
Height - Seated (Max) 0.591" (15.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

UHE1E331MPD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE1E331MPD Payment Methods





















UHE1E331MPD Shipping Methods













If you have any question about UHE1E331MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com