

UHE1H100MDD

equest a Quote

UHE1H100MDD Information

-		
	Part Number	UHE1H100MDD
www.hei9ener.com	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 10UF 20% 50V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHE1H100MDD Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLifetine Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseKadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLied Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UHE1H100MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance10µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsSom @ 100HzRipple Current - Low Frequency55mA @ 120HzImpedance1.5 OhmsLad Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzImpedance1.5 OhmsLad Spacing0.079° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Siz / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Category	Capacitors
SeriesUHECapacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzImpedance1.5 OhmsLead Spacing0.197" Dia (5.00mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 100kHzImpedance1.5 OhmsLead Spacing0.197° (2.00mm)Size / Dimension0.49° (12.50mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UHE
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	10µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzImpedance1.00mA @ 100kHzLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzImpedance1.00mA @ 100kHzLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	Voltage - Rated	50V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzBipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40° C ~ 105° C
Ripple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In PropositionInternational PropositionRipple Current - High Frequency100mA @ 100kHzImpedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance1.5 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	55mA @ 120Hz
IILead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	100mA @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	1.5 Ohms
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHE1H100MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE1H100MDD Payment Methods



UHE1H100MDD Shipping Methods



If you have any question about UHE1H100MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com