



UHE1J121MPD6 Information



For Reference Only

Part Number UHE1J121MPD6

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 120UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHE1J121MPD6 Specifications

Manufacturer Part Number UHE IJ121MPD6 Manufacturer Nichicon Category Capacitors Package Radial, Can Series UHE Capacitance 120µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	-	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UHE Capacitance 120μF Tolerance ±20% Voltage - Rated 63 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UHE1J121MPD6
Aluminum Electrolytic Capacitors Package Radial, Can UHE Capacitance UHE Capacitance 120µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UHE Capacitance 120μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UHE Capacitance 120µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 120μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UHE
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency280mA @ 120HzRipple Current - High Frequency400mA @ 100kHzImpedance310 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.630" (16.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	120μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 400mA @ 120Hz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 7000 Hrs @ 105°C -40°C ~ 105°C -40°C -40°C ~ 105°C -40°C ~ 105°C -40°C -	Voltage - Rated	63V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 400mA @ 120Hz Ripple Current - High Frequency John Search John	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	7000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency A00mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 400mA @ 100kHz Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 310 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance310 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.630" (16.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	280mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	400mA @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.630" (16.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	310 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.630" (16.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHE1J121MPD6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE1J121MPD6 Payment Methods



















UHE1J121MPD6 Shipping Methods













If you have any question about UHE1J121MPD6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com