

UHE1V222MHD

UHE1V222MHD Information

	Part Number	UHE1V222MHD	
www.housener.com	Manufacturer	Nichicon	同产多同
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 2200UF 20% 35V RADIAL	- <i>22.</i> 2657.
	Package	Radial, Can	
/		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHE1V222MHD Specifications

Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UHE Capacitance 2200µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 3.45A @ 100kHz Impedance 17 mOhms Lead Spacing 0.630° Dia (16.00mm) Size / Dimension 1.240° (31.50mm) Meight - Seated (Max) 1.240° (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance200µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-0000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.45A @ 100kHzImpedance1.7 mOhmsLied Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.240° (31.50mm)Surface Mount Land Size-Mounting TypeRiokage / CasePackage / CaseRatin Can	Manufacturer Part Number	UHE1V222MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance2200μFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsCarofa @ 120HzRipple Current - Low Frequency3.45A @ 100kHzImpedance17 mOhmsLad Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.240° (31.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance200µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications2.76A @ 120HzRipple Current - High Frequency3.45A @ 100kHzImpedance0.295° (7.50mm)Siz / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.240° (31.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Category	Capacitors
SeriesUHECapacitance2200µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension1.240° (31.50mm)Height - Seated (Max)1.240° (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension1.240" (31.50mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzImpedance17 mOhmsLead Spacing0.630" Dia (16.00mm)Size / Dimension1.240" (31.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UHE
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension1.240" (31.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	2200µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzBipple Current - High Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzRipple Current - High Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzRipple Current - High Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzRipple Current - High Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 120HzRipple Current - High Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency2.76A @ 120HzRipple Current - High Frequency3.45A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance17 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.76A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.45A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	17 mOhms
Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.240" (31.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHE1V222MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE1V222MHD Payment Methods



UHE1V222MHD Shipping Methods



If you have any question about UHE1V222MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com