

UHE1V332MHT6

UHE1V332MHT6 Information

www.hetepter.com	Part Number	UHE1V332MHT6	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	1.4.3
	Description	CAP ALUM 3300UF 20% 35V RADIAL	- 1826 - A
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHE1V332MHT6 Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance3300µFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency3.376A @ 120HzImpedance14 mOhmsLied Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)3.398° (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance3300µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLied Spacing0.295" (7.50mm)Siz / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UHE1V332MHT6
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHECapacitance3300µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsS376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLad Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHECapacitance3300µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolariGeneral PurposeRiple Current - Low Frequency3.376A @ 120HzRiple Current - High Frequency0.295° (7.50mm)Size / Dimension0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUHECapacitance3300µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzInpedance1.4mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.295° (7.50mm)Height - Seated (Max)3.98" (35.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKalia, Can		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension1.398" (35.50mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Pokage / CaseKadi, Can	Series	UHE
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension1.398" (35.50mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	3300µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzBipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency3.376A @ 120HzRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency4.22A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	3.376A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	4.22A @ 100kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	14 mOhms
Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.398" (35.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHE1V332MHT6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHE1V332MHT6 Payment Methods





If you have any question about UHE1V332MHT6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com