

UHN0J222MPD3

UHN0J222MPD3 Information

Heisener.com	Part Number Manufacturer Category Description Package	UHN0J222MPD3 Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 2200UF 20% 6.3V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHN0J222MPD3 Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHNCapacitance200µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance11 mOhmsLied Spacing0.394" Dia (10.00mm)Size / Dimension0.689" (17.50mm)Sirace Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageKadial, CanSeriesUHNCapacitance200µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplications-Ripple Current - Low Frequency-Impedance11 mOhmsLied Spacing0.991″ (5.00mm)Size / Dimension0.394″ Dia (10.00mm,Height - Seated (Max)0.689″ (17.50mm)Surface Mount Land Size-Package / CaseRatia, Can	Manufacturer Part Number	UHN0J222MPD3
Aluminum Electrolytic CapacitorsPackageRadial, CanPackageUHNCapacitance200μFTolerance420%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature2000 Hrs @ 105°CPolarizationFolarApplicationsGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency11 mOhmsLad Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Size / Dimension0.689" (17.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHNCapacitance200μFTolerance420%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature2000 Hrs @ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance11 mOhmsLad Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Strace Mount Land Size-Mounting TypeHolePackage / CaseKadial, Can	Category	Capacitors
SeriesUHNCapacitance2200µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Imedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarrigationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UHN
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Lead Spacing11 mOhnsLead Spacing0.394" Dia (10.00mm)Size / Dimension0.689" (17.50mm)Hight - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	2200µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.689" (17.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 11 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.689" (17.50mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance11 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
IILead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	11 mOhms
Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
.	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHN0J222MPD3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHN0J222MPD3 Payment Methods



UHN0J222MPD3 Shipping Methods



If you have any question about UHN0J222MPD3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com