

# UHV0J221MDD

### **UHV0J221MDD Information**

www.haisener.com	Part Number	UHV0J221MDD
	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 220UF 20% 6.3V RADIAL
	Package	Radial, Can
. )		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **UHV0J221MDD Specifications**

Manufacturer Nichicon   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can   Series UHV   Capacitance 20µF   Tolerance ±20%   Voltage - Rated 6.3V   ESR (Equivalent Series Resistance) -   Lifetime @ Temp. 5000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency 360mA @ 100kHz   Impedance 230 mOhms   Lead Spacing 0.79° (2.00mn)   Size / Dimension 0.197" Dia (5.00mm)   Height - Seated (Max) 0.492" (12.50mm)   Surface Mount Land Size -   Mounting Type Through Hole	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUHVCapacitance20µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLied Spacing0.197" Dia (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UHV0J221MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHVCapacitance220µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.197° Dia (5.00mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHVCapacitance220µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.197° Dia (5.00mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Category	Capacitors
SeriesUHVCapacitance220µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency360mA @ 100kHzInpedance230 mOhmsLead Spacing0.197" Dia (5.00mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzInpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKadia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.197" Dia (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	UHV
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.197" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	220µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeFarcage / CasePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
AARipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency360mA @ 100kHzImpedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance230 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	180mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	360mA @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	230 mOhms
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UHV0J221MDD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UHV0J221MDD Payment Methods**



# **UHV0J221MDD Shipping Methods**



If you have any question about UHV0J221MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com