



UHV0J471MED Information

sener.com

Part Number UHV0J471MED

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 6.3V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHV0J471MED Specifications

Manufacturer Part Number UHV0I471MED Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UHV Capacitance 470μF Tolerance ±20% Voltage - Rated 6.3 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UHV Capacitance 470µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency S50mA @ 120Hz Ripple Current - High Frequency 100 mOhms Lead Spacing 100 mOhms Lead Spacing 100 mOhms Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UHV0J471MED
Package Radial, Can Series UHV Capacitance 470µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UHV Capacitance 470μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UHV Capacitance 470µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UHV
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 550mA @ 120Hz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Roon Hrs @ 105°C -40°C ~	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 100 mOhms Lead Spacing 52e / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar -40°C ~ 105°C -40°	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency S50mA @ 120Hz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 105°C -40°C ~ 10	Voltage - Rated	6.3V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 275mA @ 120Hz Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 550mA @ 100kHz Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 100 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance100 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	275mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	550mA @ 100kHz
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	100 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHV0J471MED Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHV0J471MED Payment Methods



















UHV0J471MED Shipping Methods













If you have any question about UHV0J471MED, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com