

UHV1A122MPD

equest a Quote

UHV1A122MPD Information

www.eesaner.com	Part Number	UHV1A122MPD	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
_//	Description	CAP ALUM 1200UF 20% 10V RADIAL	
	Package	Radial, Can	
1		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHV1A122MPD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHVCapacitance1200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarRipple Current - Low Frequency90mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Surface Mount Land Size-Package / CaseManufacuentPackage / CaseSatial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUHVCapacitance1200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.689" (17.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UHV1A122MPD
Aluminum Electrolytic CapacitorsPackageRadial, CanPackageUHVCapacitance1200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Derating Temperature6000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CPolarization40°C ~ 105°CRiple Current - Low Frequency90mA @ 120HzRiple Current - High Frequency30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Package/ CaseKalia, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHVCapacitance1200µFColorance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUHVCapacitance1200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzSize / Dimension0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Strace Mount Land Size-Package / CaseRidial, Can		Aluminum Electrolytic Capacitors
Capacitance1200μFFolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzMapedance30 mOhmsSize / Dimension0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKaila, Can	Package	Radial, Can
Folerance±20%Folerance10VVoltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Series	UHV
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Package / CaseRidil, Can	Capacitance	1200µF
Constraint-ESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)-Clifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeFacuage / CasePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarPolarizationsGeneral PurposeApplications990mA @ 120HzRipple Current - Low Frequency990mA @ 120HzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRatial, Can	Voltage - Rated	10V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	6000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency990mA @ 120HzRipple Current - High Frequency1.65A @ 100kHzImpedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance30 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	990mA @ 120Hz
IILead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.65A @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	30 mOhms
Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UHV1A122MPD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHV1A122MPD Payment Methods



UHV1A122MPD Shipping Methods



If you have any question about UHV1A122MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com