

UHW0J682MHD6

UHW0J682MHD6 Information

w Artic Fer.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UHW0J682MHD6 Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Operating Temperature10000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (1.600mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime Temp.10000 Hrs @ 105°COperating Temperature9olarApplicationsGeneral PurposeRipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLied Spacing0.630° Dia (16.00mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Pokage / CaseMang HolePokage / CaseRadial, Can	Manufacturer Part Number	UHW0J682MHD6
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUHWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzRipple Current - High Frequency3.795A @ 100kHzImpedance0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUHWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications2.86A @ 120HzRipple Current - Low Frequency3.795A @ 100kHzImpedance14 mOhmsLad Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUHWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzImpedance14 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzImpedance14 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.866° (22.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency2.86A @ 120HzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Hight - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseKadia (Can	Series	UHW
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	6800µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzNipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzRipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
And -40°C ~ 105°C Polarization Polar Applications Polar Applications General Purpose Ripple Current - Low Frequency 2.86A @ 120Hz Mappleace 3.795A @ 100kHz Impedance 14 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzRipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.86A @ 120HzRipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency2.86A @ 120HzRipple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency3.795A @ 100kHzImpedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance14 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.86A @ 120Hz
IILead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.795A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	14 mOhms
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can
		Report errors?

UHW0J682MHD6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UHW0J682MHD6 Payment Methods



UHW0J682MHD6 Shipping Methods



If you have any question about UHW0J682MHD6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com