



UKA1H101MPD Information



For Reference Only

Part Number UKA1H101MPD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UKA1H101MPD Specifications

Manufacturer Part Number UKA1H101MPD Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UKA Capacitance 100μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polar Audio Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Manuting Type Through Hole		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UKA Capacitance 100µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Manufacturer Part Number	UKA1H101MPD
PackageRadial, CanSeriesUKACapacitance100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency190mA @ 120HzRipple Current - High Frequency285mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-	Manufacturer	Nichicon
Package Radial, Can Series UKA Capacitance 100µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Category	Capacitors
Series UKA Capacitance 100μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance100μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency190mA @ 120HzRipple Current - High Frequency285mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Series	UKA
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size -55°C ~ 105°C -0105°C -0108°C -0	Voltage - Rated	50V
Operating Temperature -55°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size -	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 285mA @ 10kHz Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 190mA @ 120Hz 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 285mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Applications	Audio
Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	190mA @ 120Hz
Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	285mA @ 10kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) Surface Mount Land Size 0.512" (13.00mm) -	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size -	Size / Dimension	0.315" Dia (8.00mm)
	Height - Seated (Max)	0.512" (13.00mm)
Mounting Type Through Hole	Surface Mount Land Size	-
Mounting Type	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UKA1H101MPD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UKA1H101MPD Payment Methods



















UKA1H101MPD Shipping Methods













If you have any question about UKA1H101MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com