

UKA1H470MED

UKA1H470MED Information

For Reference Only	Part Number	UKA1H470MED	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 47UF 20% 50V RADIAL	- \$5352854
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	062774
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UKA1H470MED Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKACapacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationAudioApplications115mA @ 120HzRipple Current - High Frequency30mA @ 10kHzImpedance-Lied Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseKaial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKACapacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature9olarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency300mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Size / Dimension-Mounting Type-Package / CaseMain CanPackage / CaseAidia, Can	Manufacturer Part Number	UKA1H470MED
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKACapacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUKACapacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsXudioRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.428" Dia (6.30mm)Strace Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUKACapacitance47μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzInpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzInpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)-Nounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzBipple Current - High Frequency0.098" (2.50mm)Impedance-Lead Spacing0.448" Dia (6.30mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	UKA
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	47µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationAudioApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsAudioApplicationsAudioRipple Current - Low Frequency115mA @ 120HzRipple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
IT enderIt for a field of a fi	Polarization	Polar
Ripple Current - High Frequency230mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	115mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	230mA @ 10kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors [*]	Package / Case	Radial, Can
		Report errors?

UKA1H470MED Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UKA1H470MED Payment Methods



UKA1H470MED Shipping Methods



If you have any question about UKA1H470MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com