

# UKL0J103MHD

Request a Quote

## **UKL0J103MHD Information**

	Part Number	UKL0J103MHD	
	Manufacturer	Nichicon	
wit wheteener com	Category	Capacitors Aluminum Electrolytic Capacitors	
6.8	Description	CAP ALUM 10000UF 20% 6.3V RADIAL	
er/	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UKL0J103MHD** Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance10000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.9A @ 120HzImpedance-Lied Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance1000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295° (7.50mn)Size / Dimension1.634° (41.50mm)Height - Seated (Max)1.634° (41.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can	Manufacturer Part Number	UKL0J103MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance10000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.634" (41.50mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUKLCapacitance1000µFTolerance-20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.185A @ 10kHzImpedance.19A @ 120HzLiad Spacing0.295° (7.50mm)Siz / Dimension0.709° Dia (18.00mm)Height - Seated (Max).634° (41.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUKLCapacitance10000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance10000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension1.634°(41.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension1.634°(41.50mm)Height - Seated (Max)1.634°(41.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UKL
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.634" (41.50mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Capacitance	10000µF
For the series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.634" (41.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzBipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}$ C ~ $85^{\circ}$ C
Ripple Current - Low Frequency1.9A @ 120HzRipple Current - High Frequency2.185A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Indext of the product of the produc	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.9A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	2.185A @ 10kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.634" (41.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.634" (41.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can
		Report errors?

### **UKL0J103MHD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UKL0J103MHD Payment Methods**



# **UKL0J103MHD Shipping Methods**



If you have any question about UKL0J103MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com