

UKL1E681MHD

UKL1E681MHD Information

	Part Number	UKL1E681MHD
	Manufacturer	Nichicon
v. whet oter.com	Category	Capacitors Aluminum Electrolytic Capacitors
Re	Description	CAP ALUM 680UF 20% 25V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UKL1E681MHD Specifications

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>
CategoryCapacitorsAluninum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance680µFTolerance±20%Voltage - Rated5VSER (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature+40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipe Current - Low Frequency810mA @ 120Hz
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance680µFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating TemperaturePolarPolarizationSeries CalenationApplicationsGeneral PurposeRippe Current - Low Frequency810m A @ 120Hz
PackageRadial, CanSeriesUKLCapacitance680μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRippe Current - Low Frequency810mA @ 120Hz
SeriesUKLCapacitance680µFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRippe Current - Low Frequency810mA @ 120Hz
Capacitance680µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temper2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRippe Current - Low Frequency810mA @ 120Hz
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
ApplicationsGeneral PurposeRipple Current - Low Frequency810mA @ 120Hz
Ripple Current - Low Frequency810mA @ 120Hz
Ripple Current - High Frequency1.215A @ 10kHz
Impedance -
Lead Spacing 0.197" (5.00mm)
Size / Dimension 0.492" Dia (12.50mm)
Height - Seated (Max) 1.043" (26.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors ⁵

UKL1E681MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UKL1E681MHD Payment Methods



UKL1E681MHD Shipping Methods



If you have any question about UKL1E681MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com