

## UKL1V102MHD

## **UKL1V102MHD Information**

berUKL1V102MHDurerNichiconCapacitorsAluminum Electrolytic CapacitorsonCAP ALUM 1000UF 20% 35V RADIALRadial, CanFor the pricing/inventory/lead time, please contactus	
Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote
	<ul> <li>wrer Nichicon         <ul> <li>Capacitors</li> <li>Aluminum Electrolytic Capacitors</li> </ul> </li> <li>on CAP ALUM 1000UF 20% 35V RADIAL         <ul> <li>Radial, Can</li> <li>For the pricing/inventory/lead time, please contact us</li> <li>Website: https://www.heisener.com</li> </ul> </li> </ul>



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **UKL1V102MHD Specifications**

ManufacturerNichiconCapacitorsCapacitorsPackageRadial, CanPackageRadial, CanStriesUKLCapacitance1000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature6eneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.1A @ 120HzImpedance-Lied Spacing0.295° (7.50mm)Siz / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance1000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzRipple Current - High Frequency.265A @ 10kHzImpedance-Lead Spacing0.630° Dia (16.00mm)Size / Dimension1.043° (26.50mm)Height - Seated (Max).14043° (26.50mm)Surface Mount Land Size-Package / CaseRiogh HolePackage / CaseRiogh HolePackage / CaseRatial, Can	Manufacturer Part Number	UKL1V102MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance1000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzInpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUKLCapacitance1000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications1.1A @ 120HzRipple Current - High Frequency1.265A @ 10kHzImpedance0.205° (7.50mm)Siz / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeHolePackage / CaseKalial, Can	Category	Capacitors
SeriesUKLCapacitance1000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzImpedance-Lead Spacing0.630" Dia (16.00mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UKL
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.043" (26.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	1000µF
ESR-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzRipple Current - High Frequency1.265A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzRipple Current - High Frequency1.265A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzRipple Current - High Frequency1.265A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 120HzRipple Current - High Frequency1.265A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.1A @ 120HzRipple Current - High Frequency1.265A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Indext of the section of the sectio	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.1A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.265A @ 10kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### **UKL1V102MHD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UKL1V102MHD Payment Methods**



## **UKL1V102MHD Shipping Methods**



If you have any question about UKL1V102MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com