

UKL2A221MHD

UKL2A221MHD Information

| UKL2A221MHD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 100V RADIAL Radial, Can For the pricing/inventory/lead time, please contact | |
|---|---|
| Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |
| | lichicon Capacitors Auminum Electrolytic Capacitors CAP ALUM 220UF 20% 100V RADIAL Cadial, Can For the pricing/inventory/lead time, please contact s Vebsite: https://www.heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UKL2A221MHD Specifications

| ManufacturerNichiconCapacitorsCapacitorsPackageRadial, CanPackageRadial, CanSeriesUKLCapacitance20µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency870mA @ 120HzRipple Current - High Frequency920°T, 7.50mm)Size / Dimension0.295°T, 7.50mm)Size / Dimension1.043°L (26.50mm)Height - Seated (Max)1.043°L (26.50mm)Surface Mount Land Size-Package / CaseKadia, Can | - | |
|--|------------------------------------|----------------------------------|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageKLCapacitance20µFColerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency850mA @ 120HzRipple Current - High Frequency970mA @ 10kHzImpedance-Lead Spacing0.295°(7.50mm)Siz / Dimension0.630° Dia (16.00mm,Height - Seated (Max)1.043° (26.50mm,Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can | Manufacturer Part Number | UKL2A221MHD |
| Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKLCapacitance220µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Package / CaseRadial, Can | Manufacturer | Nichicon |
| PackageRadial, CanSeriesUKLCapacitance20\u03cfFTolerance±20\u03cfVoltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRiple Current - Low Frequency580mA @ 120HzRiple Current - High Frequency630°D iai (16.00mm)Siz / Dimension0.295° (7.50mm)Siz / Dimension0.40°C astronomHeight - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Package / CaseKadial, Can | Category | Capacitors |
| SeriesUKLCapacitance220µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzNipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can | | Aluminum Electrolytic Capacitors |
| Capacitance220μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Polaring TypeThrough HolePackage / CaseRatial, Can | Package | Radial, Can |
| Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low FrequencyS80mA @ 120HzRipple Current - High Frequency.Broma @ 100KHz.Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can | Series | UKL |
| Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency870mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.043" (26.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pockage / CaseRatial, Can | Capacitance | 220µF |
| Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzBipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.043" (26.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can | Tolerance | ±20% |
| Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can | Voltage - Rated | 100V |
| Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can | ESR (Equivalent Series Resistance) | - |
| PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lifetime @ Temp. | 2000 Hrs @ 85°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Operating Temperature | -40°C ~ 85°C |
| AARipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Polarization | Polar |
| In a constraint of the second secon | Applications | General Purpose |
| Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - Low Frequency | 580mA @ 120Hz |
| Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - High Frequency | 870mA @ 10kHz |
| Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Impedance | - |
| Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lead Spacing | 0.295" (7.50mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Size / Dimension | 0.630" Dia (16.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can | Height - Seated (Max) | 1.043" (26.50mm) |
| Package / Case Radial, Can | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can |
| | | Report errors? |

UKL2A221MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UKL2A221MHD Payment Methods



UKL2A221MHD Shipping Methods



If you have any question about UKL2A221MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com