



UKT0J470MDD Information



For Reference Only

Part Number UKT0J470MDD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UKT0J470MDD Specifications

Manufacturer Part NumberUKT0J470MDDManufacturerNichiconCategoryCapacitorsPackageRadial, CanSeriesUKTCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency130mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-	•	
Category Capacitors Package Radial, Can Series UKT Capacitance 47µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Manufacturer Part Number	UKT0J470MDD
PackageRadial, CanSeriesUKTCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency130mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)	Manufacturer	Nichicon
PackageRadial, CanSeriesUKTCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency130mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)	Category	Capacitors
SeriesUKTCapacitance $47μF$ Tolerance $\pm 20\%$ Voltage - Rated $6.3V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $1000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsAudioRipple Current - Low Frequency $65mA @ 120Hz$ Ripple Current - High Frequency $130mA @ 10kHz$ Impedance-Lead Spacing $0.079" (2.00mm)$ Size / Dimension $0.197" \text{ Dia } (5.00mm)$ Height - Seated (Max) $0.433" (11.00mm)$		Aluminum Electrolytic Capacitors
Capacitance 47µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Series	UKT
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 10kHz Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) 6.3V 6.3V 6.3V 6.3V 6.3V 6.3V 6.3V 6.3V 6.3V 6.405°C 6.5m 6.105°C 7.000m 6.5m 6.100m 6.100	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) - 1000 Hrs @ 105°C -55°C ~ 105°C Polar -05°C 105°C 100°C 10	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) 1000 Hrs @ 105°C -55°C ~ 105°C Polar Audio 65mA @ 120Hz 130mA @ 120Hz 130mA @ 10kHz - 0.079" (2.00mm) 0.197" Dia (5.00mm)	Voltage - Rated	6.3V
Operating Temperature -55°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) -55°C ~ 105°C Audio 0.079°C 120Hz 130mA @ 120Hz 130mA @ 10kHz	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 10kHz Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) Audio Audio 65mA @ 120Hz 130mA @ 10kHz - 0.079" (2.00mm) 0.433" (11.00mm)	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Applications	Audio
Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Ripple Current - Low Frequency	65mA @ 120Hz
Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Ripple Current - High Frequency	130mA @ 10kHz
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm)	Impedance	-
Height - Seated (Max) 0.433" (11.00mm)	Lead Spacing	0.079" (2.00mm)
-	Size / Dimension	0.197" Dia (5.00mm)
Surface Mount Land Size	Height - Seated (Max)	0.433" (11.00mm)
Durinee Frount Durie Dide	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UKT0J470MDD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UKT0J470MDD Payment Methods



















UKT0J470MDD Shipping Methods













If you have any question about UKT0J470MDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com