



UKT0J470MDD Information



For Reference Only

Part Number UKT0J470MDD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UKT0J470MDD Specifications

Manufacturer Part Number UKT01470MDD Manufacturer Nichicon Category Capacitors Package Radial, Can Series UKT Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UKT Capacitance UKT Capacitance 47µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ingedance Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	UKT0J470MDD
PackageRadial, CanSeriesUKTCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency130mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
Package Radial, Can Series UKT Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UKT Capacitance 47µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UKT
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 120Hz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 8 Adial, Can	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 120Hz Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 105°C -55°C ~ 105°C -105°C -105°C	Voltage - Rated	6.3V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Audio
Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	65mA @ 120Hz
Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	130mA @ 10kHz
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.433" (11.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UKT0J470MDD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UKT0J470MDD Payment Methods



















UKT0J470MDD Shipping Methods













If you have any question about UKT0J470MDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com