



### **UKW1E153MRD Information**

Part Number UKW1E153MRD

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 15000UF 20% 25V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UKW1E153MRD Specifications**

Manufacturer Part Number         UKW1E153MRD           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can           Series         UKW           Capacitance         15000µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         Audio           Ripple Current - Low Frequency         3.8A @ 120Hz           Ripple Current - High Frequency         4.37A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.969" (50.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	•	
Category         Capacitors           Package         Radial, Can           Series         UKW           Capacitance         15000μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         Audio           Ripple Current - Low Frequency         3.8A @ 120Hz           Ripple Current - High Frequency         4.37A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.969" (50.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UKW1E153MRD
Package         Radial, Can           Series         UKW           Capacitance         15000µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         Audio           Ripple Current - Low Frequency         3.8A @ 120Hz           Ripple Current - High Frequency         4.37A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.969" (50.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UKW           Capacitance         15000μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Audio           Applications         Audio           Ripple Current - Low Frequency         3.8A @ 120Hz           Ripple Current - High Frequency         4.37A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.969" (50.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UKW           Capacitance         15000μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         Audio           Ripple Current - Low Frequency         3.8A @ 120Hz           Ripple Current - High Frequency         4.37A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.969" (50.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         15000µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         Audio           Ripple Current - Low Frequency         3.8A @ 120Hz           Ripple Current - High Frequency         4.37A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.969" (50.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 25V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications Audio  Ripple Current - Low Frequency 3.8A @ 120Hz  Ripple Current - High Frequency 4.37A @ 10kHz  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 1.969" (50.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UKW
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.37A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	15000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  Audio  Ripple Current - Low Frequency  3.8A @ 120Hz  Ripple Current - High Frequency  4.37A @ 10kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  1.969" (50.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  Audio  Ripple Current - Low Frequency  Ripple Current - High Frequency  4.37A @ 10kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 85°C  -40°C ~ 85°C  Audio  Audio  Audio  Audio  3.8A @ 120Hz  4.37A @ 10kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  5.866" Dia (22.00mm)  1.969" (50.00mm)  Through Hole  Radial, Can	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 4.37A @ 10kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio  Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz  Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  3.8A @ 120Hz  Ripple Current - High Frequency  4.37A @ 10kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  1.969" (50.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Operating Temperature	-40°C ∼ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  4.37A @ 10kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  1.969" (50.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance	Applications	Audio
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	3.8A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	4.37A @ 10kHz
Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 1.969" (50.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.969" (50.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report offors.		Report errors?

#### **UKW1E153MRD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UKW1E153MRD Payment Methods**



















### **UKW1E153MRD Shipping Methods**













If you have any question about UKW1E153MRD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com