

UKZ2A100MPM

UKZ2A100MPM Information

www.meisener.com	Part Number Manufacturer Category Description Package	UKZ2A100MPM Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 10UF 20% 100V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UKZ2A100MPM Specifications

ManufacturerNichiconCapacitorsCapacitorsPackageRadial, CanPackageRadial, CanStriesUKZCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioApplications-Ripple Current - High Frequency-Impedance0.138° (3.50mm)Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.453° (11.50mm)Surface Mount Land Size-Mounting TypeFinegatencePackage / CaseKaial, Can		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKZCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationAudioApplications-Ripple Current - Low Frequency-Impedance-Lifedime Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Package / CaseThrough HolePackage / CaseRadia, Can	Manufacturer Part Number	UKZ2A100MPM
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKZCapacitance10µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance0.138° (3.50mm)Size / Dimension0.315° Dia (8.00mm)Size / Dimension0.453° (11.50mm)Surface Mount Land Size-Polarig TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUKZCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency-Impedance-Lad Spacing0.138° (3.50mm)Size / Dimension0.315° Dia (8.00mm)Size / Dimension0.453° (11.50mm)Surface Mount Land Size-Polaring TypeRadial, Can	Category	Capacitors
SeriesUKZCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency-Ingedance-Lied Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Pounting TypeRikal CanPokage / CaseRatial, Can		Aluminum Electrolytic Capacitors
CapacitanceI0µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature+40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.415" Dia (8.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Toterance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.453° (11.50mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UKZ
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.435" (11.50mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeFrequenctPackage / CaseRatial, Can	Capacitance	10µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.453" (11.50mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioAipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Apple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsAudioRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsAudioApplications-Ripple Current - Low Frequency-Apple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
IIRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.453" (11.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.453" (11.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Depart among 2	Package / Case	Radial, Can
Report errors?		Report errors?

UKZ2A100MPM Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UKZ2A100MPM Payment Methods



UKZ2A100MPM Shipping Methods



If you have any question about UKZ2A100MPM, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com