

ULD2D2R2MED

ULD2D2R2MED Information

www.helsener.com	Part Number Manufacturer Category Description	ULD2D2R2MED Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 2.2UF 20% 200V RADIAL	
	Package	Radial, Can For the pricing/inventory/lead time, please contact us	首都思
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ULD2D2R2MED Specifications

ManufacturerNichiconCagacitorsAluminum Electrolytic CagacitorsPackageRadial, CanPackageRadial, CanSeriesULDCapacitance2.2µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplications-Ripple Current - High Frequency-Impedance-Lied Spacing0.098" (2.50mm)Size / Dimension0.948" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesULDCapacitance2.2µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Sirace Mount Land Size-Mounting TypeFacial CanPackage / CaseRatial, Can	Manufacturer Part Number	ULD2D2R2MED
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesULDCapacitance2.2µFTolerance2.20%Voltage - Rated000VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature4.0°C ~ 105°CPolarizationGeneral PurposeApplications-Ripple Current - High Frequency-Ripple Current - High Frequency0.098° (2.50mm)Siz / Dimension0.248° Dia (6.30mm)Siz / Dimension0.492° (12.50mm)Sirace Mount Land Size-Mounting TypeFrequencyPackage / CaseStail, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesULDCapacitance2.2µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications-Ripple Current - High Frequency-Impedance0.098" (2.50mm)Liad Spacing0.248" Dia (6.30mm)Size / Dimension0.492" (12.50mm)Strace Mount Land Size-Mounting TypeFinough HolePackage / CaseKaila, Can	Category	Capacitors
SeriesULDCapacitance2.2μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Lifed Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Pounting TypeRipagh Land SizePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance2.2µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeFhrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pokage / CaseRidi, Can	Series	ULD
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	2.2µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pounting TypeFriough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	12000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

ULD2D2R2MED Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ULD2D2R2MED Payment Methods



ULD2D2R2MED Shipping Methods



If you have any question about ULD2D2R2MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com