

## ULE-3.3/20-D24P-C

## ULE-3.3/20-D24P-C Information

|     | com            | <br>ULE-3.3/20-D24P-C<br>Murata Power Solutions Inc.<br>Power Supplies - Board Mount<br>DC DC Converters<br>DC/DC CONVERT 3.3V 20A<br>8-DIP Module, 1/8 Brick<br>For the pricing/inventory/lead time, please contact<br>us |                 |
|-----|----------------|--|-----------------|
| For | Reference Only | Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com  | Request a Quote |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## ULE-3.3/20-D24P-C Specifications

| -                        |  |
|--------------------------|--|
| Manufacturer Part Number | ULE-3.3/20-D24P-C                                      |
| Manufacturer             | Murata Power Solutions Inc.                            |
| Category                 | Power Supplies - Board Mount                           |
|                          | DC DC Converters                                       |
| Package                  | 8-DIP Module, 1/8 Brick                                |
| Series                   | ULE  |
| Туре                     | Isolated Module  |
| Number of Outputs        | 1  |
| Voltage - Input (Min)    | 18V  |
| Voltage - Input (Max)    | 36V  |
| Voltage - Output 1       | 3.3V   |
| Voltage - Output 2       | -  |
| Voltage - Output 3       | -  |
| Voltage - Output 4       | -  |
| Current - Output (Max)   | 20A  |
| Power (Watts)            | 66W  |
| Voltage - Isolation      | 2.25kV (2250V)   |
| Applications             | ITE (Commercial)                                       |
| Features                 | Remote On/Off, OCP, OTP, SCP, UVLO                     |
| Operating Temperature    | $-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$      |
| Efficiency               | 89%  |
| Mounting Type            | Through Hole   |
| Package / Case           | 8-DIP Module, 1/8 Brick                                |
| Size / Dimension         | 2.22" L x 0.89" W x 0.41" H (56.4mm x 22.6mm x 10.4mm) |
|                          |  |

| Supplier Device Package            |   |                                     |  |  |  |  |  |
|------------------------------------|---|-------------------------------------|--|--|--|--|--|
| Control Features                   | -<br>Enable, Active High  |                                     |  |  |  |  |  |
| Control realures                   | Enable, Active High   | Deport orreg                        |  |  |  |  |  |
|                                    |   | Report errors?                      |  |  |  |  |  |
| ULE-3.3/20-D24P-C Guarantees       |   |                                     |  |  |  |  |  |
| QUALITY We<br>GUARANTEE If th      | Quality Guarantees<br>We provide 90 days warranty. *<br>If the items you received were not in perfect quality, we would be responsible for your refund or<br>replacement, but the items must be returned in their original condition. |                                     |  |  |  |  |  |
| GUARANTEE We                       | Service Guarantees<br>We guarantee 100% customer satisfaction.<br>Our experienced sales team and tech support team back our services to satisfy all our customers.  |                                     |  |  |  |  |  |
| ULE-3.3/20-D24P-C Payment Methods  |   |                                     |  |  |  |  |  |
| Stransfer P                        | ayPal WESTERN WU<br>moving money for better Some MoneyGram Alipays VISA   | tercard Processor Discover UnionPay |  |  |  |  |  |
| ULE-3.3/20-D24P-C Shipping Methods |   |                                     |  |  |  |  |  |
| _21                                |   | IN ALL INFORM                       |  |  |  |  |  |

If you have any question about ULE-3.3/20-D24P-C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com