

## ULS-3.3/30-D48PH-C

#### ULS-3.3/30-D48PH-C Information



| Part Number  | ULS-3.3/30-D48PH-C   |
|--------------|--|
| Manufacturer | Murata Power Solutions Inc.  |
| Category     | Power Supplies - Board Mount<br>DC DC Converters   |
| Description  | DC/DC CONVERT 3.3V 30A   |
| Package      | 8-DIP Module, 1/16 Brick   |
|              | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com |



Request a Quote

For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### ULS-3.3/30-D48PH-C Specifications

| Manufacturer Part Number | ULS-3.3/30-D48PH-C                                     |  |  |  |
|--------------------------|--|--|--|--|
| Manufacturer             | Murata Power Solutions Inc.                            |  |  |  |
| Category                 | Power Supplies - Board Mount                           |  |  |  |
|                          | DC DC Converters                                       |  |  |  |
| Package                  | 8-DIP Module, 1/16 Brick                               |  |  |  |
| Series                   | ULS  |  |  |  |
| Туре                     | Isolated Module  |  |  |  |
| Number of Outputs        | 1  |  |  |  |
| Voltage - Input (Min)    | 36V  |  |  |  |
| Voltage - Input (Max)    | 75V  |  |  |  |
| Voltage - Output 1       | 3.3V   |  |  |  |
| Voltage - Output 2       | -  |  |  |  |
| Voltage - Output 3       | -  |  |  |  |
| Voltage - Output 4       | -  |  |  |  |
| Current - Output (Max)   | 30A  |  |  |  |
| Power (Watts)            | 100W   |  |  |  |
| Voltage - Isolation      | 2.25kV (2250V)   |  |  |  |
| Applications             | ITE (Commercial)                                       |  |  |  |
| Features                 | Remote On/Off, OTP, OVP, SCP, UVLO                     |  |  |  |
| Operating Temperature    | $-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$      |  |  |  |
| Efficiency               | 91%  |  |  |  |
| Mounting Type            | Through Hole   |  |  |  |
| Package / Case           | 8-DIP Module, 1/16 Brick                               |  |  |  |
| Size / Dimension         | 1.30" L x 0.90" W x 0.40" H (33.0mm x 22.9mm x 10.2mm) |  |  |  |
|                          |  |  |  |  |

| Control Features Enable, Active High | III S. 3 3/30-D48PH-C Guarantees |                     |  |  |                |  |
|--------------------------------------|----------------------------------|---------------------|--|--|----------------|--|
|                                      |                                  |                     |  |  | Report errors? |  |
|                                      | Control Features                 | Enable, Active High |  |  |                |  |
| Supplier Device Package -            | Supplier Device Package          | -                   |  |  |                |  |

## ULS-3.3/30-D48PH-C Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# ULS-3.3/30-D48PH-C Payment Methods



If you have any question about ULS-3.3/30-D48PH-C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com