

# UMA1H0R1MDD

### **UMA1H0R1MDD** Information

4		Part Number	UMA1H0R1MDD	
	C.	Manufacturer	Nichicon	
	www.heleoper.com	Category	Capacitors Aluminum Electrolytic Capacitors	
		Description	CAP ALUM 0.1UF 20% 50V RADIAL	- 38 - 186 - 1
		Package	Radial, Can	
	/		For the pricing/inventory/lead time, please contact us	E1634854
	For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UMA1H0R1MDD Specifications**

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>	-	
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, CanSeriesUMACapacitance0.1µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ S5°COperating Temperature000 Hrs @ S5°CPolarizationPolarApplicationsGeneral PurposeRippe Current - High FrequencyImA @ 120 HzImpedance.Liad Spacing0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Hight - Seated (Max)0.53° (0.00mm)Surface Mount Land Size.Mounting Type-Package / CaseMain Land SizeSize / CaseSize / CaseSize / CaseSize / CaseSize / CaseSize / Case	Manufacturer Part Number	UMA1H0R1MDD
IdentifyAlumina Electrolytic CapacitorsPackageRadial, CanSeriesUMACapacitance0.1µFTolerance20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Derating Temper2000 Hrs @ 85°COperating TemperatureAu°c ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hog FrequencyIn A @ 120HzRippe Current - High Frequency0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Size / Dimension0.35° (0.00mm)Size / Dimension0.35	Manufacturer	Nichicon
PackageRadial, CanSeriesUMACapacitance0.1µFTolerance20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Johren Grenp,000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolaranceApplicationsGeneral PurposeRipple Current - Hog Frequency1.5mA @ 10kHzRippe Agencing0.55° (1.50mm)Siz / Dimension0.157° Dia (4.00mm)Siz / Dimension0.35° (6.00mm)Sirder Muttand Size-Surface Mount Land Size-Mutting TypeHolePokage / CaseStali Can	Category	Capacitors
SeriesUMACapacitance0.1µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolariFolaryApplicationsGeneral PurposeRipple Current - Low FrequencyImA @ 120HzImpedance-Lead Spacing0.55° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.236° (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePokange / CaseKalia , Can		Aluminum Electrolytic Capacitors
Capacitance0.1µFTolerance±20%Voltage Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ St°COperating Temperature40°C ~ 85°CPolarFolarizationApplicationsGeneral PurposeRipple Current - High Frequency1.5mA @ 10kHzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.236° (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High FrequencyImA @ 120HzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Bight - Seated (Max)0.236° (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Series	UMA
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low FrequencyImA @ 120HzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	0.1µF
EVE-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low FrequencyImA @ 120HzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low FrequencyImA @ 120HzRipple Current - High Frequency.Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.236" (6.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low FrequencyImA @ 120HzBipple Current - High Frequency1.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low FrequencyImA @ 120HzRipple Current - High Frequency1.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeApplicationsImA @ 120HzRipple Current - Low Frequency1.5mA @ 10kHzMipedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low FrequencyImA @ 120HzRipple Current - High Frequency1.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.5mA @ 10kHz
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.236" (6.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

#### **UMA1H0R1MDD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UMA1H0R1MDD Payment Methods**



## **UMA1H0R1MDD** Shipping Methods



If you have any question about UMA1H0R1MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com