

UMJ0J220MDL

UMJ0J220MDL Information

Heisener.com	Part Number Manufacturer Category Description Package	UMJ0J220MDL Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 22UF 20% 6.3V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UMJ0J220MDL Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUMJCapacitance22µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Operating Temperature1000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency28mA @ 120HzImpedance-Lead Spacing0.055° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.205° (5.20mm)Surface Mount Land Size-Mounting TypeFincuga HalePackage / CaseMaila, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUMJCapacitance22µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Operating Temperature1000 Hrs @ 85°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency28mA @ 120HzNipple Current - High Frequency0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Size / Dimension0.55° (1.50mm)Height - Seated (Max)0.505° (1.50mm)Surface Mount Land Size-Mounting Type-Package / CaseMang HolePackage / CaseAgai, Can	Manufacturer Part Number	UMJ0J220MDL
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUMJCapacitance22µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency28mA @ 120HzRipple Current - High Frequency0.059" (1.50mm)Size / Dimension0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Hight - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUMJCapacitance22µFTolerance-20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Joher Series1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzRipple Current - High Frequency0.05°P (1.50mm)Siz / Dimension0.157° Dia (4.00mm)Siz / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.20° (5.20mm)Surface Mount Land Size-Mounting TypeFolared MailPackage / CaseRadial, Can	Category	Capacitors
SeriesUMJCapacitance22µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolariFolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance22µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.205° (5.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	UMJ
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	22µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzNippedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.059" (1.50mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzRipple Current - High Frequency42mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzBipple Current - High Frequency42mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28mA @ 120HzRipple Current - High Frequency42mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsGeneral PurposeApplicationsSema @ 120HzRipple Current - Low Frequency42mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Ripple Current - Low Frequency28mA @ 120HzRipple Current - High Frequency42mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	28mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	42mA @ 10kHz
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.205" (5.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.205" (5.20mm)
Package / Case Radial, Can	Surface Mount Land Size	-
.	Mounting Type	Through Hole
Report errors [*]	Package / Case	Radial, Can
		Report errors?

UMJ0J220MDL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UMJ0J220MDL Payment Methods



UMJ0J220MDL Shipping Methods



If you have any question about UMJ0J220MDL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com