

UMK105CH820KV-F

UMK105CH820KV-F Information



For Reference Only

Part Number UMK105CH820KV-F

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 82PF 50V C0H 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UMK105CH820KV-F Specifications

Manufacturer Part Number UMK105CH820KV-F Manufacturer Taiyo Yuden Category Capacitors Package 0402 (1005 Metric) Series M Capacitance 82pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0402 (1005 Metric) Series M Capacitance 82pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Manufacturer Part Number	UMK105CH820KV-F
Package 0402 (1005 Metric) Series M Capacitance 82pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Manufacturer	Taiyo Yuden
Package 0402 (1005 Metric) Series M Capacitance 82pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Category	Capacitors
Series M Capacitance 82pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 82pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Package	0402 (1005 Metric)
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Series	M
Voltage - Rated50VTemperature CoefficientC0HOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.022" (0.55mm)Lead Spacing-Lead Style-	Capacitance	82pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.022" (0.55mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Temperature Coefficient	СОН
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.022" (0.55mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

UMK105CH820KV-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UMK105CH820KV-F Payment Methods



















UMK105CH820KV-F Shipping Methods













If you have any question about UMK105CH820KV-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com