

UMV0G470MFD

UMV0G470MFD Information

www.heisener.com	Part Number Manufacturer Category Description	UMV0G470MFD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 47UF 20% 4V RADIAL	
	Package	Radial, Can For the pricing/inventory/lead time, please contact us	ÔXH
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UMV0G470MFD Specifications

Manufacturer Part NumberUMV0G470MFDManufacturerNichiconCategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUMVCapacitance4/µFTolerance±20%Voltage - Rated4VESR (Equivalent Series Resistance)-Operating Temperature5000 Hrs @ 105°COparing Temperature6000 Hrs @ 105°CApplicationsGeneral PurposeRipple Current - High Frequency6007 @ 2007	-	
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, CanSeriesUMVCapacitance47µFTolerance±20%Voltage - Rated4VESR (Equivalent Series Resistance)-Derating Temperature5000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency6Ripple Current - High Frequency-Impedance0.079°(2.00mm)Size / Dimension0.197° Dia (5.00mm)Hight - Seated (Max)0.36°(6.00mm)Surface Mount Land Size-	Manufacturer Part Number	UMV0G470MFD
IdentifyAluminut Electrolytic CapacitorsPackageRadial, CanSeriesUMVCapacitance47µFTolerance±20%Voltage - Rated4VSSR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency36mA @ 120HzInpedance-Lided Spacing0.079°(2.00mm)Size / Dimension0.197° Diat.000mm)Size / Dimension0.326°(6.00mm)Surface Mount Land Size-Surface Mount Land Size-	Manufacturer	Nichicon
PackageRadial, CanSeriesUMVCapacitance47µFTolerance±20%Yoltage - Rated4VESR (Equivalent Series Resistance)-Jeftrime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency36MA @ 120HZInpedance.Lad Spacing0.079°(2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.236° (6.00mm)Surface Mount Land Size.	Category	Capacitors
SeriesUMVCapacitance47μFTolerance±20%Voltage - Rated4VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarization6eneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency.Impedance-Lad Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size.		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated4VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency36mA @ 120HzImpedance-Ikad Spacing0.079° (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Package	Radial, Can
Tolerance±20%Voltage - Rated4VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Series	UMV
Voltage - Rated4VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Capacitance	47µF
FSR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Voltage - Rated	4V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Polarization	Polar
InInRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Ripple Current - Low Frequency	36mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size -	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size -	Size / Dimension	0.197" Dia (5.00mm)
	Height - Seated (Max)	0.236" (6.00mm)
Mounting Type Through Hole	Surface Mount Land Size	-
inough file	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors [®]		Report errors?

UMV0G470MFD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UMV0G470MFD Payment Methods



UMV0G470MFD Shipping Methods



If you have any question about UMV0G470MFD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com