



UP025CH3R3D-A-BZ Information

Heisener.com

Part Number UP025CH3R3D-A-BZ

ManufacturerTaiyo YudenCategoryCapacitors

Ceramic Capacitors

Description CAP CER 3.3PF 50V CH AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UP025CH3R3D-A-BZ Specifications

Manufacturer Part NumberUP025CH3R3D-A-BZManufacturerTaiyo YudenCategoryCapacitorsPackageAxialSeries-Capacitance3.3pFTolerance±0.5pFVoltage - Rated50VTemperature CoefficientCHOperating Temperature-25°C ~ 85°CFeatures-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxial
Category Capacitors Ceramic Capacitors Package Axial Series - Capacitance 3.3pF Tolerance ±0.5pF Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole
Package Axial Series - Capacitance 3.3pF Tolerance ±0.5pF Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Package Axial Series - Capacitance 3.3pF Tolerance ±0.5pF Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Series - Capacitance 3.3pF Tolerance ±0.5pF Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Capacitance 3.3pF Tolerance ±0.5pF Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Tolerance ±0.5pF Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Voltage - Rated 50V Temperature Coefficient CH Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Temperature Coefficient Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole
Applications General Purpose Failure Rate - Mounting Type Through Hole
Failure Rate - Mounting Type Through Hole
Mounting Type Through Hole
Package / Case Axial
Size / Dimension 0.079" Dia x 0.091" L (2.00mm x 2.30mm)
Height - Seated (Max) -
Thickness (Max) -
Lead Spacing -
Lead Style -
Report errors?

UP025CH3R3D-A-BZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UP025CH3R3D-A-BZ Payment Methods



















UP025CH3R3D-A-BZ Shipping Methods













If you have any question about UP025CH3R3D-A-BZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com