

## UP050CH6R8K-KFC

### **UP050CH6R8K-KFC Information**

Heisener.com

Part Number UP050CH6R8K-KFC

Manufacturer Taiyo Yuden Category Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 6.8PF 50V C0H AXIAL

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UP050CH6R8K-KFC Specifications**

Manufacturer Part Number         UP050CH6R8K-KFC           Manufacturer         Taiyo Yuden           Category         Capacitors           Package         Axial           Series         -           Capacitance         6.8pF           Tolerance         ±10%           Voltage - Rated         50V           Temperature Coefficient         C0H           Operating Temperature         -25°C ~ 85°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         Axial           Series         -           Capacitance         6.8pF           Tolerance         ±10%           Voltage - Rated         50V           Temperature Coefficient         C0H           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	UP050CH6R8K-KFC
Package         Axial           Series         -           Capacitance         6.8pF           Tolerance         ±10%           Voltage - Rated         50V           Temperature Coefficient         C0H           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer	Taiyo Yuden
Package         Axial           Series         -           Capacitance         6.8pF           Tolerance         ±10%           Voltage - Rated         50V           Temperature Coefficient         C0H           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         -           Capacitance         6.8pF           Tolerance         ±10%           Voltage - Rated         50V           Temperature Coefficient         C0H           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         6.8pF           Tolerance         ±10%           Voltage - Rated         50V           Temperature Coefficient         C0H           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Package	Axial
Tolerance ±10%  Voltage - Rated 50V  Temperature Coefficient COH  Operating Temperature -25°C ~ 85°C  Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing - Lead Style -	Series	-
Voltage - Rated50VTemperature CoefficientC0HOperating Temperature-25°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.087" Dia x 0.126" L (2.20mm x 3.20mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	6.8pF
Temperature Coefficient Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COH OOH COH COH COH COH COH COH COH COH	Tolerance	±10%
Operating Temperature-25°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.087" Dia x 0.126" L (2.20mm x 3.20mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - General Purpose - General Purpose - Through Hole - Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) - Thickness (Max) - Lead Spacing - Case - Cas	Temperature Coefficient	СОН
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-25°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type  Package / Case  Axial  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  Through Hole  Axial  0.087" Dia x 0.126" L (2.20mm x 3.20mm)  - Case (Max)	Applications	General Purpose
Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.087" Dia x 0.126" L (2.20mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### **UP050CH6R8K-KFC Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **UP050CH6R8K-KFC Payment Methods**





















### **UP050CH6R8K-KFC Shipping Methods**













If you have any question about UP050CH6R8K-KFC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com