



UP050SL300J-A-B Information

Heisener.com

Part Number UP050SL300J-A-B

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 30PF 50V SL AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UP050SL300J-A-B Specifications

| Category Capacitors Package Axial Series - Capacitance 30pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - | | |
|--|--------------------------|---|
| Category Capacitors Package Axial Series - Capacitance 30pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Manufacturer Part Number | UP050SL300J-A-B |
| Package Axial Series - Capacitance 30pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Manufacturer | Taiyo Yuden |
| Package Axial Series - Capacitance 30pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Category | Capacitors |
| Series - Capacitance 30pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | | Ceramic Capacitors |
| Capacitance 30pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Package | Axial |
| Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Series | - |
| Voltage - Rated Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Lead Spacing - Lead Style 50V SL ON SI ON SI SI SI SI SI SI SI SI SI S | Capacitance | 30pF |
| Temperature Coefficient Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - SL Operating Temperature -25°C ~ 85°C | Tolerance | ±5% |
| Operating Temperature Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - - | Voltage - Rated | 50V |
| Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Maxing Size / | Temperature Coefficient | SL |
| Ratings - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style | Operating Temperature | -25°C ~ 85°C |
| Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) Lead Spacing Lead Style - | Features | - |
| Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Ratings | - |
| Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Applications | General Purpose |
| Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Failure Rate | - |
| Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Mounting Type | Through Hole |
| Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - | Package / Case | Axial |
| Thickness (Max) - Lead Spacing - Lead Style - | Size / Dimension | 0.087" Dia x 0.126" L (2.20mm x 3.20mm) |
| Lead Spacing - Lead Style - | Height - Seated (Max) | - |
| Lead Style - | Thickness (Max) | - |
| · | Lead Spacing | - |
| Report errors? | Lead Style | - |
| | | Report errors? |

UP050SL300J-A-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UP050SL300J-A-B Payment Methods



















UP050SL300J-A-B Shipping Methods













If you have any question about UP050SL300J-A-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com