



UP050SL330J-KEC Information

Heisener.com

Part Number UP050SL330J-KEC

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 33PF 50V SL AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UP050SL330J-KEC Specifications

Manufacturer Part Number UP050SL330J-KEC Manufacturer Taiyo Yuden Category Capacitors Package Axial Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	UP050SL330J-KEC
Package Axial Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	Taiyo Yuden
Package Axial Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 33pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±5% Voltage - Rated 50V Temperature Coefficient SL Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Series	-
Voltage - Rated50VTemperature CoefficientSLOperating Temperature-25°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.087" Dia x 0.126" L (2.20mm x 3.20mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	33pF
Temperature Coefficient Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - SL - SSC - SS	Tolerance	±5%
Operating Temperature-25°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.087" Dia x 0.126" L (2.20mm x 3.20mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	50V
Features Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Temperature Coefficient	SL
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-25°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Through Hole Axial 0.087" Dia x 0.126" L (2.20mm x 3.20mm) - Case (Max)	Applications	General Purpose
Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.087" Dia x 0.126" L (2.20mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

UP050SL330J-KEC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UP050SL330J-KEC Payment Methods



















UP050SL330J-KEC Shipping Methods













If you have any question about UP050SL330J-KEC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com