



# UP050UJ200J-A-B Information

Heisener.com

Part Number UP050UJ200J-A-B

Manufacturer Taiyo Yuden Category Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 20PF 50V U2J AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UP050UJ200J-A-B Specifications**

Category         Capacitors           Package         Axial           Series         -           Capacitance         20pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         U2J           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -		
Category         Capacitors           Package         Axial           Series         -           Capacitance         20pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         U2J           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	UP050UJ200J-A-B
Package         Axial           Series         -           Capacitance         20pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         U2J           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer	Taiyo Yuden
Package         Axial           Series         -           Capacitance         20pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         U2J           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         -           Capacitance         20pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         U2J           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         20pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         U2J           Operating Temperature         -25°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.087" Dia x 0.126" L (2.20mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Package	Axial
Tolerance ±5%  Voltage - Rated 50V  Temperature Coefficient U2J  Operating Temperature -25°C ~ 85°C  Features Ratings Applications General Purpose  Failure Rate Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm)  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style	Series	-
Voltage - Rated  Temperature Coefficient  U2J  Operating Temperature  -25°C ~ 85°C  Features  - Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Through Hole  Package / Case  Axial  Size / Dimension  0.087" Dia x 0.126" L (2.20mm x 3.20mm)  Height - Seated (Max)  - Thickness (Max)  Lead Spacing  - Lead Style  -  Value  U2J  U2J  U2J  U2J  U2J  U2J  U2J  U2	Capacitance	20pF
Temperature Coefficient  Operating Temperature  -25°C ~ 85°C  Features  - Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Through Hole  Package / Case  Axial  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  U2J  U2J  025°C ~ 85°C  - 86°C	Tolerance	±5%
Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Voltage - Rated	50V
Features - General Purpose - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Lead Spacing - Lead Style - General Purpose - General	Temperature Coefficient	U2J
Ratings - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-25°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Applications	General Purpose
Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.087" Dia x 0.126" L (2.20mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

### UP050UJ200J-A-B Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## UP050UJ200J-A-B Payment Methods



















# **UP050UJ200J-A-B Shipping Methods**













If you have any question about UP050UJ200J-A-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com