



UP050UJ220J-A-B Information

Heisener.com

Part Number UP050UJ220J-A-B

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 22PF 50V U2J AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UP050UJ220J-A-B Specifications

Manufacturer Part Number UP050UJ220J-A-B Manufacturer Taiyo Yuden Category Capacitors Package Axial Series - Capacitance 22pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient UJ Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series - Capacitance 22pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	UP050UJ220J-A-B
Package Axial Series - Capacitance 22pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	Taiyo Yuden
Package Axial Series - Capacitance 22pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 22pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 22pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±5% Voltage - Rated 50V Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Series	-
Voltage - Rated Temperature Coefficient U2J Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) Thickness (Max) Lead Spacing - Lead Style	Capacitance	22pF
Temperature Coefficient Operating Temperature -25°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - U2J U2J 025°C ~ 85°C - 86°C	Tolerance	±5%
Operating Temperature-25°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.087" Dia x 0.126" L (2.20mm x 3.20mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - General Purpose - General Purpose - Through Hole - Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) - Thickness (Max) - Lead Spacing - General Size / Dimension - General Purpose - Gener	Temperature Coefficient	U2J
Ratings - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-25°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	General Purpose
Package / Case Axial Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.087" Dia x 0.126" L (2.20mm x 3.20mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.087" Dia x 0.126" L (2.20mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

UP050UJ220J-A-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UP050UJ220J-A-B Payment Methods



















UP050UJ220J-A-B Shipping Methods













If you have any question about UP050UJ220J-A-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com