

# **UP1-UZZZ-CSG**

### **UP1-UZZZ-CSG Information**

For Reference Only	Part Number Manufacturer Category Description Package	UP1-UZZZ-CSG Vicor Corporation Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 28V 1200W - For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UP1-UZZZ-CSG Specifications**

ManufacturerVicor CorporationCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesMicroPACSpriesMicroPACNumber of Outputs1Solage - Output 185 ~ 264 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Soltation-Voltage - Soltati			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesMicroPACTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 4-Power (Watts)1200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting Type7.45° L x 4.00° W x 1.72° H (189.2mm x 101.6mm x 43.7mm)	Manufacturer Part Number	UP1-UZZZ-CSG	
AC DC ConvertersPackage-SeriesMicroPACTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 51200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting Type7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Manufacturer	Vicor Corporation	
Package-SeriesMicroPACStropACEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 44.9AVoltage - Output 4100WVoltage - Output 4100WPower (Watts)ITE (Commercial)Voltage - Isolation-Fefficiency92%Operating Temperature-O°C ~ 65°C (With Derating). Remote Sense, Standby Output, Universal InputFeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         MicroPAC           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Output 4         -           Current - Output (Max)         42.9A           Power (Watts)         1200W           Voltage - Isolation         -           Efficiency         92%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         DC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)		AC DC Converters	
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Output 5         -           Voltage - Output 6         -           Voltage - Output 7         -           Voltage - Output 8         -           Voltage - Output 9         -           Voltage - Soltion 4         -           Voltage - Isolation 5         -           Voltage - Isolation 5         -           Voltage - Isolation 6         -           Efficiency 7         92%           Operating Temperature 7         -20°C ~ 65°C (With Derating)           Features 7         DC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal Input 7           Mounting Type 7         Chassis Mount           Size / Dimension 7         -  <	Package	-	
Number of Outputs         I           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         42.9A           Power (Watts)         1200W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         92%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         DC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Series	MicroPAC	
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Output 4         -           Voltage - Output 4         -           Current - Output (Max)         42.9A           Power (Watts)         1200W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         92%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         DC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Туре	Enclosed	
Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Output 4         -           Current - Output (Max)         42.9A           Power (Watts)         1200W           Applications         ITE (commercial)           Voltage - Isolation         -           Efficiency         92%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         DC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Number of Outputs	1	
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)42.9APower (Watts)1200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting Type7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Voltage - Input	ge - Input 85 ~ 264 VAC	
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)42.9APower (Watts)1200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Voltage - Output 1	28V	
Voltage - Output 4-Current - Output (Max)42.9APower (Watts)1200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Voltage - Output 2	-	
Current - Output (Max)42.9APower (Watts)1200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)Pounting TypeDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting Type7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Voltage - Output 3	-	
Power (Watts)1200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Current - Output (Max)	42.9A	
Voltage - Isolation-Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Power (Watts)	1200W	
Efficiency92%Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Applications	ITE (Commercial)	
Operating Temperature-20°C ~ 65°C (With Derating)FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Voltage - Isolation	-	
FeaturesDC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Efficiency	92%	
Mounting Type         Chassis Mount           Size / Dimension         7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Operating Temperature	$-20^{\circ}C \sim 65^{\circ}C \text{ (With Derating)}$	
Size / Dimension         7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	Features	DC Input Capable, Load Sharing, Remote Sense, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	7.45" L x 4.00" W x 1.72" H (189.2mm x 101.6mm x 43.7mm)	
		Report errors?	

#### **UP1-UZZZ-CSG Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UP1-UZZZ-CSG Payment Methods**



## **UP1-UZZZ-CSG Shipping Methods**



If you have any question about UP1-UZZZ-CSG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com