

UPA1A332MHD

UPA1A332MHD Information

ww.ur.etscher.com	Part Number Manufacturer Category Description Package	UPA1A332MHD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 3300UF 20% 10V RADIAL Radial, Can	
	Гаскаде	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPA1A332MHD Specifications

Manufacturer Part NumberUPA1A322MHDManufacturer ANichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanStriesUPACapacitance300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.938A @ 120HzIpedance0.927 Dia (1.50mm)Size A Diamission0.927 Dia (1.50mm)Size A Diamission0.927 Dia (1.50mm)Size A Diamission-Height - Seated (Max)0.637 (2.70mm)Surface Mount Land Size-Mounting TypeHrough HolePackage / Case-Mounting Type-Height - Seated (Max)-Surface None Land Size-Anone Land Size-Anon	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPACapacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.938 A @ 120HzImpedance2.28A @ 100kHzLied Spacing0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.663" (27.00mm)Surface Mount Land Size-Youring TypeThrough HolePackage / CaseKadia, Can	Manufacturer Part Number	UPA1A332MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPACapacitance3300µFTolerance±20%Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.28A @ 100kHzImpedance2.200mm)Siz / Dimension0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Polaring TypeFarce Mount Land SizePolaring TypeRipal AcaPolaring TypeFarce MacaRipple CarseAdjal, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPACapacitance3300µFTolerance-20%Voltage - Rated10VESR (Equivalent Series Resistance)-Jerieme @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationFolaraceApplicationsGeneral PurposeRipple Current - Low Frequency1.938A @ 120HzImpedance2.28A @ 100kHzImpedance0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Siz / Dimension0.492" Dia (12.50mm)Sirafe Mount Land Size-Mounting TypeFolareatPackage / CaseMaid, Can	Category	Capacitors
SeriesUPACapacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.28A @ 100kHzImpedance2 unOhmsLiad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePokage / CaseKaidi, Can		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.938A @ 120HzImpedance22 mOhmsLad Spacing0.197° (5.00mm)Size / Dimension0.197° (5.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia LCan	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.938A @ 120HzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UPA
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Pokage / CaseRadial, Can	Capacitance	3300µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsGeneral PurposeApple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeAipple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFroughtedPackage / CaseRadial, Can	Voltage - Rated	10V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
InInRipple Current - Low Frequency1.938A @ 120HzRipple Current - High Frequency2.28A @ 100kHzImpedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the first	Applications	General Purpose
Impedance22 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.938A @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	2.28A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	22 mOhms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPA1A332MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPA1A332MHD Payment Methods



UPA1A332MHD Shipping Methods



If you have any question about UPA1A332MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com