

## UPB2E470MHD

#### **UPB2E470MHD Information**

www.elecher.com	Part Number Manufacturer Category Description Package	UPB2E470MHD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 47UF 20% 250V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **UPB2E470MHD Specifications**

Manufacturer Part NumberUPB2E470MHDManufacturer ANichiconCategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRdial, CanSeriesUPBCapacitance4/µГTolerance200%Voltage - Rated200%ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-Applications3000 Hrs @ 105°CPolarization-ApplicationsSono A @ 100 HrzRipple Current - High Frequency300 Mar @ 100 HrzImpedance-Liad Spacing0107" (5.00mm)Size Albanciand103° (26.50mm)Hight - Seated (Max)-Munting Type-Polarized Spacing-Surface Mount Land Size-Apple Carent - Low Frequency0.103" (26.50mm)Sizer Albanciand-Sizer Albanciand-Hight - Seated (Max)-Surface Mount Land Size-Anoming Type-Polarizer Albanciand-Sizer Albanciand Sizer-Anoming Type-Polarizer Albanciand Sizer-Sizer Albanciand Sizer-Anoming Type-Polarizer Albanciand Sizer-Anoming Type-Polarizer Albanciand Sizer-Anoming Type-Polarizer Albanciand Sizer-Polarizer Albanciand Sizer-Polarizer Alban	-	
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, CanSeriesUPBCapacitance4/µFTolerance20%Voltage - Rated20VESR (Equivalent Series Resistance)-Derating Temperature5000 Hrs.@ 105°COperating Temperature25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRippe Current - High Frequency3000 Af 200 HzImpedance-Lad Spacing700mA @ 1000 HzImpedance-Lead Spacing0197" (5.00mm)Size / Dimension1043" (26.50mm)Hight - Seated (Max)-Surface Mount Land Size-Anuting TypeFinought ElectronPackage / CaseMain (26.00m)Package / CaseMain (26.00m)	Manufacturer Part Number	UPB2E470MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPBCapacitance47µFTolerance±20%Voltage - Rated500ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-ApplicationsCeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.492" Dia (12.50mm)Sirafee Mount Land Size-Mounting TypeFincuga HolePackage / CaseSadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPBCapacitance47µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFincuga HalePackage / CaseKadial, Can	Category	Capacitors
SeriesUPBCapacitance47μFTolerance±20%Voltage - Rated505VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRippe Current - Low Frequency350mA @ 120HzImpedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRippe Current - High Frequency350mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Bight - Seated (Max)-Surface Mount Land Size-Mounting TypeThough HolePackage / CaseStala, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - High Frequency350mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Hight - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UPB
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency700mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	Capacitance	47µF
ConstraintESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)5000 Hrs @ 105°CLifetime @ Temp25°C ~ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency700mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadia, CanRadia, Can	Voltage - Rated	250V
Operating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency700mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
Polarization-ApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency700mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency700mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency350mA @ 120HzRipple Current - High Frequency700mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	-
In or of the product	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	350mA @ 120Hz
Lead Spacing 0.197" (5.00mm)   Size / Dimension 0.492" Dia (12.50mm)   Height - Seated (Max) 1.043" (26.50mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can	Ripple Current - High Frequency	700mA @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPB2E470MHD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UPB2E470MHD Payment Methods**



## **UPB2E470MHD Shipping Methods**



If you have any question about UPB2E470MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com