



UPB2G220MHD Information



For Reference Only

Part Number UPB2G220MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 400V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPB2G220MHD Specifications

Manufacturer Part Number UPB2G220MHD Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UPB Capacitance 22μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature −25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UPB Capacitance 22µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Lead Spacing On.197" (5.00mm) Size / Dimension Lead Space Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	UPB2G220MHD
Package Radial, Can Series UPB Capacitance 22μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UPB Capacitance 22μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UPB Capacitance 22μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 22µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UPB
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 400mA @ 120Hz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 400mA @ 120Hz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 105°C -25°C ~ 105°C Author Commons General Purpose 200mA @ 120Hz 400mA @ 100kHz -101mm 101mm 101m	Voltage - Rated	400V
Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 200mA @ 120Hz Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 400mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing O.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 400mA @ 100kHz	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	200mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	400mA @ 100kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPB2G220MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPB2G220MHD Payment Methods



















UPB2G220MHD Shipping Methods













If you have any question about UPB2G220MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com