



UPJ1E102MHD6 Information



For Reference Only

Part Number UPJ1E102MHD6

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPJ1E102MHD6 Specifications

Manufacturer Part NumberUPJ1E102MHD6ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance1000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°C
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°C
PackageRadial, CanSeriesUPJCapacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°C
PackageRadial, CanSeriesUPJCapacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°C
Series UPJ Capacitance 1000μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C
Capacitance $1000 \mu F$ Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 5000Hrs @ 105°C
Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance) - Lifetime @ Temp. $5000 \text{Hrs} \text{@} 105 ^{\circ}\text{C}$
Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C
Lifetime @ Temp. 5000 Hrs @ 105°C
-
Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Polarization Polar
Applications General Purpose
Ripple Current - Low Frequency 1.31A @ 120Hz
Ripple Current - High Frequency 1.52A @ 10kHz
Impedance 66 mOhms
Lead Spacing 0.295" (7.50mm)
Size / Dimension 0.709" Dia (18.00mm)
Height - Seated (Max) 0.650" (16.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors

UPJ1E102MHD6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPJ1E102MHD6 Payment Methods





















UPJ1E102MHD6 Shipping Methods













If you have any question about UPJ1E102MHD6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com