



UPJ1E182MHD Information



For Reference Only

Part Number UPJ1E182MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1800UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPJ1E182MHD Specifications

Manufacturer Part Number UPI 1E182MHD Manufacturer Nichicon Category Capacitors Package Radial, Can Series UPI Capacitance 1800µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UPJ Capacitance 1800µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UPJ1E182MHD
Package Radial, Can Series UPJ Capacitance 1800μF Tolerance ±20% Voltage - Rated 25 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UPJ Capacitance 1800µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UPJ Capacitance 1800µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 1800μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UPJ
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Raidial, Can	Capacitance	1800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.96A @ 120Hz Rippedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 5000 Hrs @ 105°C 6000 Hrs @ 105° 600	Voltage - Rated	25V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.96A @ 120Hz Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency 2.18A @ 10kHz Impedance 32 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.96A @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	2.18A @ 10kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	32 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPJ1E182MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPJ1E182MHD Payment Methods



















UPJ1E182MHD Shipping Methods













If you have any question about UPJ1E182MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com