

UPJ1E391MPD

UPJ1E391MPD Information

www.undbuner.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 390UF 20% 25V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPJ1E391MPD Specifications

Manufacturer Part Number UP1E391MPD Manufacturer Nichicon Category Capacitors Category Aluninum Electrolytic Capacitors Package Radial, Can Series UPJ Capacitance 390µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Operating Temperature 5000 Hrs © 105°C Olaritations General Purpose Applications General Purpose Ripple Current - Low Frequency 770m A@ 120Hz Impedance 100 mOhrns Lad Spacing 0.394° Dia (10.00mm) Size / Dimension 0.394° Dia (10.00mm) Size / Dimension 0.394° Dia (10.00mm) Aufing Type - Autoning Type Frequency	-	
CategoryCapacitorsAluninum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance390µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature90µFOpariationsGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency985mA @ 10kHzImpedance10 mOhmsLiad Spacing0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Nounting TypeFinogationsPackage / CaseMain Can	Manufacturer Part Number	UPJ1E391MPD
IdentifyAuminu Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance390µFTolerance20%Voltage - Rated25VESR (Equivalent Series Resistance)-Operating Temperature5000 Hrs@ 105°COperating Temperature55°C ~ 105°CApplicationsGeneral PurposeApple Current - Low Frequency70mA @ 120HzRippe Current - High Frequency110 mOhmsLied Spacing0.39" Dial.0.00mm, CallSize / Dimension0.39" Dial.0.00mm, CallSize / Dimension0.39" Dial.0.00mm, CallHight - Seated (Max)0.34" Dial.0.00mm, CallSurface Mount Land Size-Auning TypeHonog HolePackage / CaseMail, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPJCapacitance30µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency985mA @ 104MzImpedance101 mOhmsLied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseMail, Can	Category	Capacitors
SeriesUPJCapacitance390µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsSize / Dimension0.394° Dia (10.00mm)Size / Dimension0.846° (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can		Aluminum Electrolytic Capacitors
Capacitance990µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-5°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLiad Spacing0.197" (5.00mm)Size / Dimension0.344" Dia (10.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can	Package	Radial, Can
Toleance±0%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Surface Mount Land Size-Mounting TypeFrequenctPackage / CaseRatial, Can	Series	UPJ
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzMipedance110 mOhmsInpedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Hounting TypeFrequencyPackage / CaseRatial, Can	Capacitance	390µF
FSR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mouning TypeFackage / CaseRadia, CanRadia, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzBippe Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 120HzBipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency770mA @ 120HzRipple Current - High Frequency985mA @ 10kHzImpedance110 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	770mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	985mA @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	110 mOhms
Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report erro		Report errors?

UPJ1E391MPD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPJ1E391MPD Payment Methods



UPJ1E391MPD Shipping Methods



If you have any question about UPJ1E391MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com