

UPJ1E820MED

UPJ1E820MED Information

www.heisener.com	Part Number Manufacturer Category Description	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 82UF 20% 25V RADIAL	
	Package	Radial, Can For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPJ1E820MED Specifications

Manufacturer Part NumberUPI1E820MEDManufacturer ANichiconCategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRdial, CanStriesUPJCapacitance8µFTolerance220%Voltage - Rated250%ESR (Equivalent Series Resistance)-Lifetime Ø Temp.2000 Hrs @ 105°COperating Temperature900 Hrs @ 105°CPolarizationPolarApplicationsSence All DataRipple Current - High Frequency85m A @ 10kHzIpdeance0098°C.50mn)Size Joinnension0.42°C 1000mn)Starfe Mount Land Size-Mounting TypeHongh HolePackage Case-Mounting TypeFrequency	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance82µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)-Derating Temperature2000 Hrs @ 105°COperating Temperature000 Hrs @ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency85m A @ 10kHzImpedance0.998° (2.50mm)Liad Spacing0.998° (2.50mm)Size / Dimension0.424° Dia (a.30mm)Height - Seated (Max)0.472° (12.00mm)Surface Mount Land Size-Pounting TypeFinough HolePackage / CaseKadia, Can	Manufacturer Part Number	UPJ1E820MED
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance\$2µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency88mA @ 120HzRipple Current - High Frequency285mA @ 10kHzImpedance0.098" (2.50mm)Siz / Dinension0.248" Dia (6.30mm)Siz / Dinension0.472" (12.00mm)Kirface Mount Land Size-Mounting TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPJCapacitance82µFTolerance-20%Voltage - Rated25VESR (Equivalent Series Resistance)-Jerieme @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationFolaranceApplicationsRenaral PurposeRipple Current - High Frequency885MA @ 10HZImpedance0.098" (2.50mm)Siz / Dinension0.248" Dia (6.30mm)Siz / Dinension0.428" Dia (6.30mm)Sirafe Mutult Land Size-Mutting TypeFolared MatePolarige Mutult Size-Size Advant Land Si	Category	Capacitors
SeriesUPJCapacitance82μFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency85MA @ 120HzImpedance470 mOhmsLiad Spacing0.98% (2.50mm)Size / Dinension0.424% 'Dia (6.30mm)Surface Mount Land Size-Mounting TypeThrough HolePokang CraseMath AgeStarface Mount Land Size-Mounting TypeRatial, Can		Aluminum Electrolytic Capacitors
Capacitance82µFTolerance±20%Voltage Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hugh Frequency825mA @ 10kHzImpedance470 mOhmsLad Spacing0.998° (2.50mm)Size / Dimension0.428° Dia (6.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - High Frequency180mA @ 120HzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UPJ
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBrippe Current - High Frequency285mA @ 10kHzImpedance-098" (2.50mm)Lead Spacing0.098" (2.50mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	82µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzMippelance285mA @ 10kHzImpedance0.098" (2.50mm)Size / Dimension0.098" (2.50mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRaid, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBipple Current - High Frequency285mA @ 10kHzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzBipple Current - High Frequency285mA @ 10kHzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency285mA @ 10kHzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency285mA @ 10kHzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-55^{\circ}C \sim 105^{\circ}C$
InInRipple Current - Low Frequency180mA @ 120HzRipple Current - High Frequency285mA @ 10kHzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency285mA @ 10kHzImpedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance470 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	180mA @ 120Hz
Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	285mA @ 10kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	470 mOhms
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPJ1E820MED Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPJ1E820MED Payment Methods



UPJ1E820MED Shipping Methods



If you have any question about UPJ1E820MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com