



### **UPJ1J820MPD Information**



For Reference Only

Part Number UPJ1J820MPD

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 82UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UPJ1J820MPD Specifications**

Manufacturer Part NumberUPJ13820MPDManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance82µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency385mA @ 120HzRipple Current - High Frequency600mA @ 10kHz
Category Capacitors Aluminum Electrolytic Capacitors  Package Radial, Can  UPJ Capacitance 82µF Tolerance ±20% Voltage - Rated 63V  ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency  Capacitors Adminum Electrolytic Capacitors  Adminum Electrolytic Capacitors  Radial, Can  UPJ  -20%  -20% -20% -20% -20%
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance82μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency385mA @ 120HzRipple Current - High Frequency600mA @ 10kHz
PackageRadial, CanSeriesUPJCapacitance82μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency385mA @ 120HzRipple Current - High Frequency600mA @ 10kHz
SeriesUPJCapacitance $82\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000  \text{Hrs} @ 105^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $385\text{mA} @ 120\text{Hz}$ Ripple Current - High Frequency $600\text{mA} @ 10\text{kHz}$
Capacitance82μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency385mA @ 120HzRipple Current - High Frequency600mA @ 10kHz
Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 385mA @ 120Hz  Ripple Current - High Frequency 600mA @ 10kHz
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  600mA @ 10kHz
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  600mA @ 10kHz
Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 385mA @ 120Hz  Ripple Current - High Frequency 600mA @ 10kHz
Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  600mA @ 10kHz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 385mA @ 120Hz  Ripple Current - High Frequency 600mA @ 10kHz
Applications General Purpose Ripple Current - Low Frequency 385mA @ 120Hz Ripple Current - High Frequency 600mA @ 10kHz
Ripple Current - Low Frequency  Ripple Current - High Frequency  600mA @ 10kHz
Ripple Current - High Frequency 600mA @ 10kHz
Impedance 220 mOhms
Lead Spacing 0.138" (3.50mm)
Size / Dimension 0.315" Dia (8.00mm)
Height - Seated (Max) 0.827" (21.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

### **UPJ1J820MPD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UPJ1J820MPD Payment Methods**



















## **UPJ1J820MPD Shipping Methods**













If you have any question about UPJ1J820MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com