

UPJ2A330MPD6

UPJ2A330MPD6 Information

-			
For Reference Only	Part Number	UPJ2A330MPD6	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	2.636
	Description	CAP ALUM 33UF 20% 100V RADIAL	- 15 91,235 A
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	EI 100-754
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPJ2A330MPD6 Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance33µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzImpedance420 mOhmsLied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance33µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzRipple Current - High Frequency93mA @ 10kHzImpedance0.197" (5.00mm)Lied Spacing0.394" Dia (10.00mm,)Size / Dimension0.394" Dia (10.00mm,)Height - Seated (Max)0.551" (14.00mm,)Surface Mount Land Size-Package / CaseKadia, Can	Manufacturer Part Number	UPJ2A330MPD6
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance33µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzRipple Current - High Frequency293mA @ 10kHzImpedance0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPJCapacitance33µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzImpedance293mA @ 10kHzLind Spacing0.197" (5.00mm)Size / Dimension0.51" (14.00mm)Size / Dimension.55" (14.00mm)Surface Mount Land Size-Mounting TypeHolePackage / CaseKadial, Can	Category	Capacitors
SeriesUPJCapacitance33μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarigationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UPJ
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzImpedance293mA @ 10kHzLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Capacitance	33µF
For the series Resistance)-ESR (Equivalent Series Resistance)5000 Hrs @ 105°CLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzBipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzBipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzBipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max).555" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzRipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency166mA @ 120HzRipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
AARipple Current - Low Frequency166mA @ 120HzRipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In PropositionPropositionRipple Current - High Frequency293mA @ 10kHzImpedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance420 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	166mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	293mA @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	420 mOhms
Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPJ2A330MPD6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPJ2A330MPD6 Payment Methods



UPJ2A330MPD6 Shipping Methods



If you have any question about UPJ2A330MPD6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com