

UPJ2E220MHD

UPJ2E220MHD Information

www.heisener.com	Part Number	UPJ2E220MHD	
	Manufacturer	Nichicon	▕ <u>ਗ਼</u> ╪੶ਖ਼ਗ਼
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 22UF 20% 250V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	ELLER STATE
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPJ2E220MHD Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance22µFTolerance±20%Voltage - Rated500 Hrs @ 105°CESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mn)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pokage / CaseRadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance22µFTolerance±20%Voltage - Rated500 Hrs @ 105°CESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mn)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pokage / CaseRadial, Can	Manufacturer Part Number	UPJ2E220MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPJCapacitance22µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency150mA @ 120HzImpedance-Lad Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Hight - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPJCapacitance22µFTolerance20%Voltage - Rated500VESR (Equivalent Series Resistance)-Operating Temperature5000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRiple Current - Low Frequency150mA @ 120HzImpedance-Lad Spacing0.25°T.50mm)Siz / Dimension0.630° Dia (16.00mm)Siz / Dimension1.043° (26.50mm)Strace Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPJCapacitance22μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance22µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension1.043° (26.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UPJ
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.043" (26.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Capacitance	22µF
Constraint-ESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzNipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	250V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzBipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
AFRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency240mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	150mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	240mA @ 10kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can
		Report errors?

UPJ2E220MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPJ2E220MHD Payment Methods



UPJ2E220MHD Shipping Methods



If you have any question about UPJ2E220MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com