

UPM1A222MHD6

UPM1A222MHD6 Information

New neisoner.com	Part Number Manufacturer Category Description Package	UPM1A222MHD6 Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 2200UF 20% 10V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPM1A222MHD6 Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.6A @ 10kHzImpedance0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseRatial, Can	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.44A @ 120HzImpedance39 mOhmsLied Spacing0.295° (7.50mn)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)0.669° (17.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRatial, Can	Manufacturer Part Number	UPM1A222MHD6
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications144A @ 120HzRipple Current - High Frequency1.6A @ 10kHzImpedance0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)0.6669° (17.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance2200µFTolerance÷20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency0.295" (7.50mm)Size / Dimension0.295" (7.50mm)Size / Dimension0.669" (11.00mm)Height - Seated (Max)0.669" (11.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUPMCapacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)0.669° (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzImpedance39 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.669° (17.00mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pokage / CaseRadial, Can	Series	UPM
Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	2200µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	10V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency1.44A @ 120HzRipple Current - High Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency1.6A @ 10kHzImpedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance39 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.44A @ 120Hz
IILead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.6A @ 10kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	39 mOhms
Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.669" (17.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can
		Report errors?

UPM1A222MHD6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPM1A222MHD6 Payment Methods



UPM1A222MHD6 Shipping Methods



If you have any question about UPM1A222MHD6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com