

# UPM1H271MPD

## **UPM1H271MPD Information**

www.hersteler.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 50V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UPM1H271MPD Specifications**

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance270µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance270μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature90mA @ 120HzPolarizationGeneral PurposeRipple Current - Low Frequency900mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLied Spacing0.197" (5.00mm)Size / Dimension1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	Manufacturer Part Number	UPM1H271MPD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance270µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance270µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRiple Current - High Frequency0197" (5.00mm)Liad Spacing0.197" (5.00mm)Size / Dimension3.34" Dia (10.00mm)Size / Dimension1.319" (33.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Category	Capacitors
SeriesUPMCapacitance270µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzInpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance270μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzInpedance55 °C hofmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Series	UPM
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	270µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFracuge / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency900mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
AARipple Current - Low Frequency900mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency1.2A @ 10kHzImpedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance65 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	900mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.2A @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	65 mOhms
Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPM1H271MPD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UPM1H271MPD Payment Methods**



# **UPM1H271MPD Shipping Methods**



If you have any question about UPM1H271MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com